



ERSKINE[™]
ATTACHMENTS, INC.

CT

Snowblower FM

Front Mount Snowblower

FEATURES

- Quick mount / dismount
- Hydraulic lift and chute rotation



Fits all tractors with or without front loader mounting bracket.



Model 601FM.



The Erskine Quick Attach Mounting System allows for easy attachment and removal of blower unit.



Front and Center...

Erskine[™] snowblowers have been proven for over 50 years by people who need to move snow fast after every snowfall or blizzard. This tough, dependable blower is built to go day after day. Features quick mount and dismount along with trouble-free chute rotation in all conditions. The Erskine[™] chews through deep drifts and clears to the bare ground.

We offer several different widths from 60" to 108", all of which are true quick attach systems that allow easy on/off attachment in approximately 5 minutes. Standard features include hydraulic lift and chute rotation, bolt-on cutting edge, and adjustable skid shoes. These ruggedly built Erskine snowblowers are second to none in features, performance, and durability.



The efficient transfer case transfers power from the rear PTO to the front mounted snowblower.



800-437-6912

www.erskineattachments.com

SKID STEER

MINI SKID STEER

COMPACT TRACTOR

Snowblower FM

- Model 601FM - #900403
- Model 721FM - #900406
- Model 781FM - #900409
- Model 901FM - #900413
- Model 960FM - #900130
- Model 1080FM - #900131




Adjustable frame system fits
all makes/models of tractors

Model 721FM with snowblower
head, frame, and transfer case

Efficient transfer case
rotates on its side
providing clearance for ease
of installation and removal

AVAILABLE OPTIONS

- Electric chute rotator (Model 601FM)
in place of hydraulic chute rotator
- Hydraulic deflector
- Electric deflector
- Hardened skid shoes
(Models 601FM / 721FM / 781FM)
(Standard on 901FM / 960FM / 1080FM)
- Optional truck loading chute
(Models 901FM / 960FM / 1080FM)



STANDARD SPECIFICATIONS

Model	1080FM	960FM	901FM	781FM	721FM	601FM
Stage	2	2	2	2	2	2
Width of Cut	108"	96"	90"	78"	72"	60"
Cutting Height	36"	36"	32"	29"	29"	27"
Auger Diameter	12" Top/18" Bottom	12" Top/18" Bottom	18" Open Flight	16" Open Flight	16" Open Flight	16" Open Flight
Fan Diameter	30" 4-Blade	30" 4-Blade	26" 4-Blade	22" 4-Blade	22" 4-Blade	20" 4-Blade
Discharge Chute	210° Hyd Rotator 1 2	210° Hyd Rotator 1 2	270° Hyd Rotator 1 2	270° Hyd Rotator 2	270° Hyd Rotator 2	270° Hyd Rotator 2
PTO Speed	540 or 1000 RPM	540 or 1000 RPM	540 or 1000 RPM	540 RPM	540 RPM	540 RPM
Casting Distance	up to 50'	up to 50'	up to 40'	up to 35'	up to 35'	up to 30'
Minimum Horsepower	85	85	50	30	30	20
Driveline Series	55	55	35	35	35	12
Cutting Edge	5/8" x 6" Bolt-on	5/8" x 6" Bolt-on	1/2" x 4" Bolt-on	1/2" x 4" Bolt-on	1/2" x 4" Bolt-on	3/8" x 3" Bolt-on
Skid Shoes	Adj. & Replaceable	Adj. & Replaceable	Adj. & Replaceable	Adj. & Replaceable	Adj. & Replaceable	Adj. & Replaceable
Shipping Weight	3300#	3245#	2250#	1660#	1630#	1050#



ERSKINE™

ATTACHMENTS, INC.

A Legacy of Excellence Since 1948

"Jesus Christ is the same yesterday and today and forever." Hebrews 13:8

Prices and specifications subject to change without notice • F.O.B. the Factory