



**ERSKINE**<sup>™</sup>  
ATTACHMENTS, INC.

CT

# Snowblower RM

## 3-Point Rear Mount PTO Snowblower

### FEATURES

- Dual auger with shear bolt protection
- 4 bolt-on replaceable hardened skid shoes
- Bolt-on cutting edge
- Standard hydraulic orbit motor chute rotator
- 4-blade fan with shear bolt protection



### Ready to Blow in Minutes...

This tough, dependable blower is built to go day after day. Features quick mount and dismount along with trouble-free chute rotation in all conditions. The blower chews through deep drifts and clears to the bare ground. We offer several different widths from 60" to 108", all of which are true quick attach systems that allow easy on/off attachment in approximately 5 minutes. Standard features include hydraulic lift and chute rotation, bolt-on cutting edge, and adjustable skid shoes. These ruggedly built snow blowers are second to none in features, performance, and durability.



**800-437-6912**

**[www.erskineattachments.com](http://www.erskineattachments.com)**

SKID STEER

MINI SKID STEER

COMPACT TRACTOR

**Snowblower RM**

Model 960RM - #900160

Model 1080RM - #900161



**No Freeze-Up Chute**  
design seals out snow  
and freezing slush

Standard hydraulic  
orbit motor chute rotator

**Efficient 4-blade**  
fan with shear bolt  
protection

Large open flight auger  
with shear bolt protection

Bolt-on, **high-carbon** steel cutting edge

**AVAILABLE OPTIONS**

- 96" Model 960RM
- 108" Model 1080RM
- Hydraulic Deflector
- Electric Deflector

**STANDARD SPECIFICATIONS**

Model	960RM	1080RM
Stage	2	2
Width of Cut	96"	108"
Cutting Height	36"	36"
Auger Diameter	12" Top/18" Bottom	12" Top/18" Bottom
Fan Diameter	30" 4-Blade	30" 4-Blade
Discharge Chute	210° Hyd. Rotator <sup>1 2</sup>	210° Hyd. Rotator <sup>1 2</sup>
PTO Speed	540 or 1000 RPM	540 or 1000 RPM
Casting Distance	up to 50'	up to 50'
Minimum Horsepower	85	85
Driveline Series	55	55
Cutting Edge	5/8" x 6" Bolt-on	5/8" x 6" Bolt-on
Skid Shoes	Adj. & Replaceable	Adj. & Replaceable
Shipping Weight	3245#	3300#

<sup>1</sup> Truck loading chute with deflector control is optional  
<sup>2</sup> Includes deflector & 3-position linkage. Hydraulic or electric is optional.



**ERSKINE**<sup>TM</sup>

ATTACHMENTS, INC.

*A Legacy of Excellence Since 1948*

*"Jesus Christ is the same yesterday and today and forever." Hebrews 13:8*

Prices and specifications subject to change without notice • F.O.B. the Factory